

## Contact insert - RC-63P1N120000 - 1603538

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Contact insert, Number of positions: 6+3, Type of contact: Male connector, Solder connection

The figure shows the 6-pos. product version

### Product Features



### Key commercial data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 pc     |
| Weight per Piece (excluding packing) | 7.64 GRM |
| Custom tariff number                 | 85389099 |
| Country of origin                    | Germany  |

### Technical data

#### General

|  |                      |
|--|----------------------|
| Insertion/withdrawal cycles mechanical             | 50                   |
| Direction of rotation of contact chamber numbering | Standard             |
| Coding   | N                    |
| Contact connection method                          | Solder connection    |
| Type of contacts                                   | Male connector       |
| Number of positions                                | 9                    |
| Contact diameter of power contacts                 | 2 mm                 |
| Litz wire cross section of power contacts min.     | 0.08 mm <sup>2</sup> |
| Litz wire cross section of power contacts max.     | 2.5 mm <sup>2</sup>  |
| Nominal current per power contact at 25°C          | 20 A                 |
| Contact diameter of signal contacts                | 1 mm                 |
| Litz wire cross section of signal contacts min.    | 0.08 mm <sup>2</sup> |

## Contact insert - RC-63P1N120000 - 1603538

### Technical data

#### General

|   |                   |
|---|-------------------|
| Litz wire cross section of signal contacts max. | 1 mm <sup>2</sup> |
| Nominal current per signal contact at 25°C      | 8 A               |

#### Material

|                    |                             |
|--------------------|-----------------------------|
| Insulator material | PBT                         |
| Contact material   | CuZn                        |
| Contact surface    | Nickel-plated, gold coating |

#### Specifications according to DIN EN 61984:2001

|  |        |
|--|--------|
| Nominal / operating voltage of power contacts  | 150 V  |
| Rated surge voltage of power contacts          | 1.5 kV |
| Surge voltage category of power contacts       | II     |
| Pollution degree of power contacts             | 3      |
| Nominal / operating voltage of signal contacts | 150 V  |
| Surge voltage category of signal contacts      | II     |
| Pollution degree of signal contacts            | 3      |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 27260701 |
| eCl@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27260701 |
| eCl@ss 6.0 | 27260708 |
| eCl@ss 7.0 | 27440312 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC001121 |
| ETIM 5.0 | EC000438 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 43172015 |
| UNSPSC 7.0901 | 43201404 |
| UNSPSC 11     | 43172015 |
| UNSPSC 12.01  | 43201404 |
| UNSPSC 13.2   | 43201404 |

# Contact insert - RC-63P1N120000 - 1603538

## Approvals

Approvals

---

Approvals

EAC

---

Ex Approvals

---

Approvals submitted


---

Approval details


|     |
|-----|
| EAC |
|-----|

## Drawings

Schematic diagram



Schematic diagram



Schematic diagram

