



Order Code	L (mm)	G (mm)	L <sub>1</sub> (mm)	Thread Size	SW
971050155	5	8,0	3,5	M 2.5	SW 5
971060155	6	8,0	4,0	M 2.5	SW 5
971070155	7	8,0	5,0	M 2.5	SW 5
971080155	8	8,0	6,0	M 2.5	SW 5
971090155	9	8,0	7,0	M 2.5	SW 5
971100155	10	8,0	8,0	M 2.5	SW 5
971110155	11	8,0	9,0	M 2.5	SW 5
971120155	12	8,0	10,0	M 2.5	SW 5
971150155	15	8,0	10,0	M 2.5	SW 5
971160155	20	8,0	10,0	M 2.5	SW 5
971180155	18	8,0	10,0	M 2.5	SW 5
971200155	20	8,0	10,0	M 2.5	SW 5
971450155	45	8,0	10,0	M 2.5	SW 5
971050365	5	8,0	3,0	M 3.0	SW 6
971060365	6	8,0	3,5	M 3.0	SW 6
971080365	8	8,0	5,0	M 3.0	SW 6
971100365	10	8,0	7,0	M 3.0	SW 6
971110365	11	8,0	7,0	M 3.0	SW 6
971120365	12	8,0	9,0	M 3.0	SW 6
971130365	13	8,0	9,0	M 3.0	SW 6
971140365	14	8,0	9,0	M 3.0	SW 6
971150365	15	8,0	10,0	M 3.0	SW 6
971160365	16	8,0	10,0	M 3.0	SW 6
971170365	17	8,0	10,0	M 3.0	SW 6
971180365	18	8,0	10,0	M 3.0	SW 6
971200365	20	8,0	10,0	M 3.0	SW 6
971250365	25	8,0	10,0	M 3.0	SW 6
971300365	30	8,0	10,0	M 3.0	SW 6
971350365	35	8,0	10,0	M 3.0	SW 6
971400365	40	8,0	10,0	M 3.0	SW 6
971500365	50	8,0	10,0	M 3.0	SW 6
971060385	6	8,0	3,5	M 3.0	SW 8
971070385	7	8,0	3,5	M 3.0	SW 8
971080385	8	8,0	5,0	M 3.0	SW 8
971090385	9	8,0	5,0	M 3.0	SW 8
971100385	10	8,0	7,0	M 3.0	SW 8
971110385	11	8,0	7,0	M 3.0	SW 8
971120385	12	8,0	9,0	M 3.0	SW 8
971130385	13	8,0	9,0	M 3.0	SW 8
971140385	14	8,0	9,0	M 3.0	SW 8
971150385	15	8,0	10,0	M 3.0	SW 8
971600385	60	8,0	10,0	M 3.0	SW 8
971070485	7	8,0	3,5	M 4.0	SW 8
971080485	8	8,0	5,0	M 4.0	SW 8
971090485	9	8,0	6,0	M 4.0	SW 8
971100485	10	8,0	7,0	M 4.0	SW 8
971110485	11	8,0	8,0	M 4.0	SW 8
971120485	12	8,0	9,0	M 4.0	SW 8
971130485	13	8,0	10,0	M 4.0	SW 8
971150485	15	8,0	10,0	M 4.0	SW 8
971200485	20	8,0	10,0	M 4.0	SW 8
971250485	25	8,0	10,0	M 4.0	SW 8
971300485	30	8,0	10,0	M 4.0	SW 8
971350485	35	8,0	10,0	M 4.0	SW 8
971400485	40	8,0	10,0	M 4.0	SW 8
971450485	45	8,0	10,0	M 4.0	SW 8
971500485	50	8,0	10,0	M 4.0	SW 8
971650485	65	8,0	10,0	M 4.0	SW 8

Flammability according to: UL94-HB

Würth Elektronik eiSos GmbH & Co. KG  
EMC & Inductive Solutions

Max-Eyth-Str. 1  
74638 Waldenburg  
Germany  
com. +49 79 42 945 - 0

www.we-online.de  
eiSos@we-online.de



CREATED DaF	CHECKED SKI	GENERAL TOLERANCE DIN ISO 2768-1m	PROJECTION METHOD 	SCALE 4 : 1
DESCRIPTION <b>AsSPaIE Plastic Spacer Stud Metric Thread int./ext.</b>		MATERIAL PA66, black		
ORDER CODE 971 xxx xx5				
SIZE xxx xxx xxx	WEIGHT xxx	STATUS Released	DATE 2014-12-08	BUSINESS UNIT eiCan
				PAGE 1 / 1

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik eiSos GmbH & Co KG products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, submarine, transportation (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. Würth Elektronik eiSos GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.