




Innovative **Technology**
for a **Connected** World



AC4490-1X1 900MHz Radio Module

THE FASTEST WAY TO WIRELESS

Laird Technologies' tiny AC4490-1x1 radio modules put the power of wireless into the smallest, most cost-sensitive applications. Despite their small size, the modules can replace a mile of cable even in harsh industrial conditions.

Using field-proven FHSS 900MHz technology that utilizes an unlicensed frequency band*, AC4490-1x1s reject interference, enable co-located system operation, and ensure data integrity.

With the help of a unique transparent protocol (RF232™), AC4490-1x1 integration is easy. OEMs simply solder the radio modules and antennas into place, then power-on. All frequency hopping, synchronization, and RF system data transmission/reception is performed by the radio module.

The AC4490-1x1's standard TTL interface provides bi-directional communication in point-to-point and point-to-multipoint networks. A number of on-the-fly control commands accommodate varying wireless applications.

FEATURES

- Smallest form factor: one inch square
- Highest 900MHz data rate: 115.2 kbps
- Operates in -40°C to +85°C temp. range
- Easiest installation: protocol included
- Extremely low power for battery operation
- Range up to 1 mile

MARKETS

- Recreation
- Utility Management

global solutions: local support™

USA: +1.800.492.2320

Europe: +44.1628.858.940

Asia: +852.2268.6567

wirelessinfo@lairdtech.com

www.lairdtech.com/wireless

FLEXIBLE RF PROTOCOL

Laird Technologies' embedded transparent protocol simplifies the OEM's integration process by providing drop-in design. As each radio module receives raw data, it manages the over-the-air protocol to assure successful communication. Headers, data packet length, and CRCs are not required. The RF232 supports simple cable-replacement to complex peer-to-peer configurations, broadcast communication to all radio modules or address packets to a specific destination using unique MAC addresses embedded in each radio module.

SPECIFICATIONS

Parameter	AC4490-1x1
Interface	SMT
Frequency band (software selectable)	902-928 MHz (North America)**
Modulation	FHSS FSK
Serial interface options	3V TTL
Serial interface data rate	Up to 115.2 Kbps
Output power (w/ 3dBi antenna)	0mW-10mW variable
Current consumption (transmit/receive)†	80mA / 28mA
Channels	Up to 48 (North America)**
Security	One-byte system ID
Voltage	3.3V
Sensitivity	-99 dB @ full RF data rate
Range (line-of-sight w/ 3dBi antenna)	Up to 1 mile (1.6 km)
Temperature	-40° to +80°C
Humidity (non-condensing)	10% to 90%
Dimensions	1.0 x 1.0 x 0.2" (2.6 x 2.6 x 0.6 cm)
Weight	< 0.5 oz (< 15 g)
Antenna	External via SMT pad

*The 900MHz band is approved in the Americas and Australia as an unlicensed spectrum subject to approval by device.

**For products and specifications suited to non-U.S. countries (e.g. Australia and Europe), please contact Laird Technologies directly.


†Current consumption assumes 50% transmitter on-time.

RF PROTOCOL MODES

- a) Communication
 - Unicast (one-to-one addressing)
 - Broadcast (one-to-multiple addressing)
- b) Acknowledgement mode (ACK)
 - API with hardware and/or software ACK indication
- c) One-beacon mode
- d) Dynamic radio data table:
 - Retains data from up to 12 radio modules

INTERFACE PROTOCOL

- a) On-the-fly radio module configuration:
 - Destination address
 - RF transmit power
 - Co-located servers
 - RF channel
 - Broadcast/addressed
- b) Raw data or transmit/receive API
- c) 9-bit serial interface mode
- d) Long range mode, enables sensitivity control
- e) A/D, D/A generic I/Os
- f) Variable baud rate
- g) RF packet size, timeout control
- h) Onboard temperature sensor
- i) Handshaking, CTS/RTS, full modem-mode available
- j) In-range indicator
- k) Error detection
 - Onboard CRC
 - Duplicate packet filtering
- l) Data encryption standard (DES)



The details contained within the document are subject to change. Download the product specification from www.lairdtech.com/wireless for the most current specification.

AC4490 1X1 is not FCC approved. Laird Technologies will assist with the approval process for high volume customers.

LWS-SPEC-AC4490 1X1 0209

Any information furnished by Laird Technologies and its agents is believed to be accurate and reliable. Responsibility for the use and application of Laird Technologies materials rests with the end user since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability, or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies terms and conditions of sale in effect from time to time, a copy of which will be furnished upon request. For further information please visit our website at www.lairdtech.com. Alternatively contact: wirelessinfo@lairdtech.com. Bluetooth® is a trademark owned by Bluetooth SIG, Inc., USA and licensed to Laird Technologies.

© 2009 All Rights Reserved. Laird Technologies is a registered trademark of Laird Technologies, Inc.