




## ISP06, ISP25, ISP40, ISP60

### DESCRIPTION

The ISP06, ISP25, ISP40 and ISP60 are Single Channel Solid State Relays (Photo MOSFET) each consists of an infrared emitting diode optically coupled to a high voltage output detector. The detector consists of a Photo Voltaic Diode Array and high voltage output MOSFETs.

This Single Channel Output configuration is equivalent to 1 Form A of Electro-mechanical Relay.



### FEATURES

- Normally Open Single Pole Single Throw Relay
- High Output Voltages 60V to 600V
- Low ON Resistance
- Low Operating Current
- High AC Isolation Voltage 5000V<sub>RMS</sub>
- Wide Operating Temperature Range
- -40°C to 85°C
- Pb Free and RoHS Compliant
- Safety Approvals Pending

### APPLICATIONS

- Industrial Controls
- Telephone/Exchange Equipment
- Measurement Equipment
- FA/OA Equipment
- Security System
- Reed Relay Replacement

### ORDER INFORMATION

- Add G after PN for 10mm lead spacing
- Add SM after PN for Surface Mount,
- Add SMT&R after PN for Surface Mount Tape & Reel

### ABSOLUTE MAXIMUM RATINGS (T<sub>A</sub> = 25°C)

#### Input Diode

Forward Current	50mA
Reverse Voltage	5V
Forward Peak Current (f=100Hz, Duty Cycle = 0.1%)	1A
Power dissipation	75mW

#### Output

	ISP06	ISP25	ISP40	ISP60
Output	60	250	400	600
Breakdown Voltage V <sub>L</sub> (V)				
Load Current I <sub>L</sub>				
Continuous (mA)	550	180	120	50
Pulse (A)	1.2	0.5	0.3	0.15
(100ms, 1 shot, V <sub>L</sub> = DC)				
Power Dissipation				500mW

#### Total Package

Isolation Voltage (R.H. = 40% - 60%, 1 min)	5000V <sub>RMS</sub>
Total Power Dissipation	550mW
Operating Temperature	-40 to 85 °C
Storage Temperature	-40 to 125 °C
Lead Soldering Temperature (10s)	260°C

#### ISOCOM COMPONENTS 2004 LTD

Unit 25B, Park View Road West, Park View Industrial Estate  
Hartlepool, Cleveland, TS25 1UD, United Kingdom  
Tel: +44 (0)1429 863 609 Fax : +44 (0)1429 863 581  
e-mail: sales@isocom.co.uk  
<http://www.isocom.com>

#### ISOCOM COMPONENTS ASIA LTD

Hong Kong Office,  
Block A, 8/F, Wah Hing Industrial mansion,  
36 Tai Yau Street, San Po Kong, Kowloon, Hong Kong.  
Tel: +852 2995 9217 Fax : +852 8161 6292  
e-mail sales@isocom.com.hk



## ISP06, ISP25, ISP40, ISP60

### Truth Table

Input	Output
ON	CLOSE
OFF	OPEN

### ELECTRICAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ unless otherwise specified)

#### INPUT

Parameter	Symbol	Test Condition	Min	Typ.	Max	Unit
Forward Voltage	$V_F$	$I_F = 10\text{mA}$		1.18	1.5	V
Reverse Current	$I_R$	$V_R = 5\text{V}$			1	$\mu\text{A}$

#### OUTPUT

Parameter	Symbol	Test Condition	Min	Typ.	Max	Unit
Off State Leakage Current	$I_{\text{leak}}$	$I_F = 0\text{mA}, V_L = \text{Max}$			1	$\mu\text{A}$
On Resistance	$R_{d(\text{ON})}$	$I_F = 10\text{mA}, I_L = \text{Max}, t = 1\text{s}$				$\Omega$
			ISP06		0.7	2.5
			ISP25		6.5	15
			ISP40		20	30
Output Capacitance	$C_{\text{out}}$	$V_L = 0\text{V}, f = 1\text{MHz}$				pF
			ISP06		85	
			ISP25		60	
			ISP40		45	
		ISP60		30		




**ISP06, ISP25, ISP40, ISP60**

**ELECTRICAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$  unless otherwise specified)**

**COUPLED**

Parameter	Symbol	Test Condition	Min	Typ.	Max	Unit	
LED Turn On Current	$I_{F(on)}$	$I_L = \text{Max}$		2.5	5	mA	
LED Turn Off Current	$I_{F(off)}$	$I_L = \text{Max}$	0.4	2.5		mA	
Turn On Time	$T_{on}$	$I_F = 10\text{mA}, I_L = \text{Max}, R_L = 200\Omega$				ms	
			ISP06		1.4		3
			ISP25		1.2		3
			ISP40		0.4		3
Turn Off Time	$T_{off}$	$I_F = 10\text{mA}, I_L = \text{Max}, R_L = 200\Omega$				ms	
			ISP06		0.05		0.5
			ISP25		0.05		0.5
			ISP40		0.05		0.5
Isolation Resistance	$R_{L-O}$	$V_{L-O} = 500\text{VDC}$	$5 \times 10^{10}$			$\Omega$	
Isolation Capacitance	$C_{L-O}$	$V = 0\text{V}, f = 1\text{MHz}$		1.5		pF	

**Turn on / Turn off Time**





## ISP06, ISP25, ISP40, ISP60




Fig 1a Load Current vs Ambient Temperature




Fig 1b Load Current vs Ambient Temperature




Fig 2a On Resistance vs Ambient Temperature




Fig 2b On Resistance vs Ambient Temperature




Fig 3a Load Current vs Load Voltage






Fig 3b Load Current vs Load Voltage




**ISP06, ISP25, ISP40, ISP60**




**Fig 4 LED Turn On Current vs  $T_A$**




**Fig 5 LED Turn Off Current vs  $T_A$**




**Fig 6a Turn On Time vs LED Forward Current**



**Fig 6b Turn On Time vs LED Forward Current**




**Fig 7 Turn Off Time vs LED Forward Current**




**Fig 8 Switching Time vs Ambient Temperature**




**ISP06, ISP25, ISP40, ISP60**



**Fig 9 LED Dropout Voltage vs  $T_A$**



**Fig 10 Off State Leakage Current vs Load Voltage**



**Fig 11 Output Capacitance vs Applied Voltage**




## ISP06, ISP25, ISP40, ISP60

### ORDER INFORMATION

ISP06, ISP25, ISP40, ISP60			
After PN	PN	Description	Packing quantity
None	ISP06, ISP25, ISP40, ISP60	Standard DIP4	100 pcs per tube
G	ISP06G, ISP25G, ISP40G, ISP60G	10mm Lead Spacing	100 pcs per tube
SM	ISP06SM, ISP25SM, ISP40SM, ISP60SM	Surface Mount	100 pcs per tube
SMT&R	ISP06SMT&R, ISP25SMT&R, ISP40SMT&R, ISP60SMT&R	Surface Mount Tape & Reel	1000 pcs per reel

### DEVICE MARKING






ISP06 denotes Device Part Number (ISP06 is used as example)  
I denotes Isocom  
Y denotes 1 digit Year code  
WW denotes 2 digit Week code






## ISP06, ISP25, ISP40, ISP60

### PACKAGE DIMENSIONS (mm)




DIP



G Form



SMD









**ISP06, ISP25, ISP40, ISP60**

**RECOMMENDED PAD LAYOUT FOR SMD (mm)**



**TAPE AND REEL PACKAGING**



Direction of feed from reel




Dimension No.	<b>A</b>	<b>B</b>	<b>Do</b>	<b>D1</b>	<b>E</b>	<b>F</b>
Dimension (mm)	10.4±0.1	4.55±0.1	1.5±0.1	1.5±0.05	1.75±0.1	7.5±0.1
Dimension No.	<b>Po</b>	<b>P1</b>	<b>P2</b>	<b>t</b>	<b>W</b>	<b>K</b>
Dimension (mm)	4.0±0.1	12.0±0.1	2.0±0.1	0.33±0.1	16.0+0.3/ -0.1	4.55±0.1



**ISP06, ISP25, ISP40, ISP60**

**IR REFLOW SOLDERING TEMPERATURE PROFILE**  
(One Time Reflow Soldering is Recommended)



Profile Details	Conditions
<b>Preheat</b> - Min Temperature ( $T_{SMIN}$ ) - Max Temperature ( $T_{SMAX}$ ) - Time $T_{SMIN}$ to $T_{SMAX}$ ( $t_s$ )	150°C 200°C 60s - 120s
<b>Soldering Zone</b> - Peak Temperature ( $T_P$ ) - Liquidous Temperature ( $T_L$ ) - Time within 5°C of Actual Peak Temperature ( $T_P - 5^\circ\text{C}$ ) - Time maintained above $T_L$ ( $t_L$ ) - Ramp Up Rate ( $T_L$ to $T_P$ ) - Ramp Down Rate ( $T_P$ to $T_L$ )	260°C 217°C 30s 60s - 100s 3°C/s max 6°C/s max
Average Ramp Up Rate ( $T_{smax}$ to $T_P$ )	3°C/s max
Time 25°C to Peak Temperature	8 minutes max



**ISOCOM**  
— — — — —  
**COMPONENTS**

## ISP06, ISP25, ISP40, ISP60

### NOTES :

- Isocom is continually improving the quality, reliability, function or design and Isocom reserves the right to make changes without further notices.
- The products shown in this publication are designed for the general use in electronic applications such as office automation equipment, communications devices, audio/visual equipment, electrical application and instrumentation.
- For equipment/application where high reliability or safety is required, such as space applications, nuclear power control equipment, medical equipment, etc., please contact our sales representatives.
- When requiring a device for any "specific" application, please contact our sales for advice.
- The contents described herein are subject to change without prior notice.
- Do not immerse device body in solder paste.



**ISOCOM**  
— — — — —  
COMPONENTS

## DISCLAIMER

ISOCOM is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing ISOCOM products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such ISOCOM products could cause loss of human life, bodily injury or damage to property.

In developing your designs, please ensure that ISOCOM products are used within specified operating ranges as set forth in the most recent ISOCOM products specifications.

\_\_\_ The ISOCOM products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These ISOCOM products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury (“Unintended Usage”). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation Instruments, traffic signal instruments, combustion control instruments, medical Instruments, all types of safety devices, etc.. Unintended Usage of ISOCOM products listed in this document shall be made at the customer’s own risk.

\_\_\_ Gallium arsenide (GaAs) is a substance used in the products described in this document. GaAs dust and fumes are toxic. Do not break, cut or pulverize the product, or use chemicals to dissolve them. When disposing of the products, follow the appropriate regulations. Do not dispose of the products with other industrial waste or with domestic garbage.

\_\_\_ The products described in this document are subject to the foreign exchange and foreign trade laws.

\_\_\_ The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by ISOCOM Components for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of ISOCOM Components or others.

\_\_\_ The information contained herein is subject to change without notice.