

Specification Sheet

Part Number: 156-00069



Heavy-Duty Fir Tree Mount Cable Tie, 15" x .3", .03"-.25" Panel Thick, PA66HIRHSUV, Black, 100/pkg

Article Number

156-00069

Type

WSIFT9A

Color

Black (BK)

Features & Benefits

- The "H" profile provides a broad surface contact to minimize the pinching of bundles.
- Heavy duty fir tree mounts are equipped with a friction tab that will hold the tie in the mount, allowing them to be preassembled prior to installation.
- Designed specifically for HellermannTyton 120 - 250 lb. cable ties for heavy duty applications.

Quantity Per

bag

Product Description

HellermannTyton heavy duty fir tree mounts are designed with heavy duty applications in mind. These are optimized for up to 3 to 1 extraction versus insertion force to make assembly fast and easy. These mounts are sold as an assembly with a cable tie.

Short Description

Heavy-Duty Fir Tree Mount Cable Tie, 15" x .3", .03"-.25" Panel Thick, PA66HIRHSUV, Black, 100/pkg

Global Part Name

WSIFT9A-PA66HIRHSUV-BK

Minimum Tensile Strength (Imperial)

120.0

Minimum Tensile Strength (Metric)

535

Length L (Imperial)

15.0

Length L (Metric)

387.0

Fixation Method

Fir Tree

Identification Plate Position

none

Tie Closure

plastic pawl

Variant

Inside Serrated

Width W (Imperial)

0.3

Width W (Metric)

7.6

Bundle Diameter Max (Imperial)

4.0

Bundle Diameter Max (Metric)

102.0

Height H (Imperial)

.75

Height H (Metric)

19.10

Panel Thickness Min(Imperial)	0.039
Panel Thickness Max(Imperial)	0.256
Panel Thickness Min (Metric)	1.0
Panel Thickness Max (Metric)	6.5
Mounting Hole Diameter D (Imperial)	0.34 - 0.36
Mounting Hole Diameter D (Metric)	8.7 - 9.2 mm
Mounting Hole Diameter D Min (Imperial)	0.34
Mounting Hole Diameter D Max (Imperial)	0.36
Mounting Hole Diameter D Max (Metric)	9.25
Disc Diameter(Metric)	21.6
Disc Diameter (Imperial)	0.85
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Operating Temperature (Metric)	-40°F to +230°F (-40°C to +110°C)
ROHS Complaint	Yes

Package Quantity(Imperial)

100

Package Quantity (Metric)

100

Customs Number

3926909987